Version: 2 (01/10/2024)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

Section 1. Identification of the substance or the mixture and of the supplier

#### 1.1 Product Identifier

Product identifier: AMBER RESIN + ROSEWOOD

Other identifiers: None

# 1.2 Relevant identified uses of the substance of mixture and uses advised against

**Product uses:** Aromatic fragrance ingredient in concentrated form to be combined with other ingredients to create a finished product. Use according to established regulatory guidelines. For Manufacturing Use Only.

# 1.3 Details of the supplier of the safety data sheet

Company name: Lark Artisan Supply Inc 395 Montcalm Ave

Company address: Victoria, BC V8Z 4S8

E-Mail address: hello@larksupply.ca

Company phone: 250.701.6506

1.4 Emergency telephone number

**Emergency phone:** North America 800.424.9300/ International 703.527.3887

### Section 2. Hazards identification

### 2.1 Classification of the substance or mixture

Class and category of Sensitization - Skin Category 1

danger: Hazardous to the Aquatic Environment - Acute Hazard Category 2

Hazardous to the Aquatic Environment - Long-term Hazard Category 2

H317, May cause an allergic skin reaction.

H411, Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Signal word: Warning

**Hazard statements:** H317, May cause an allergic skin reaction.

H411, Toxic to aquatic life with long lasting effects.

**Precautionary** P261, Avoid breathing vapour or dust.

**statements:** P272, Contaminated work clothing should not be allowed out of the workplace.

P273, Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection. P302/352, IF ON SKIN: Wash with plenty of soap and water.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P363, Wash contaminated clothing before reuse.





Version: 2 (01/10/2024)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

P391, Collect spillage.

P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.

Pictograms:

2.3 Other hazards

Other hazards: None

# Section 3. Composition / information on ingredients

# 3.2 Mixtures

# **Contains:**

Name	CAS	%	GHS Classification
Ethylene brassylate	105-95-3	10-<20%	Aquatic Acute 2;H401
Benzyl benzoate	120-51-4	5-<10%	Acute Tox. 4-Aquatic Acute 1-Aquatic Chronic 2;H302-H313-H400-H411
3-(5,5,6-Trimethylbicyclo[2.2.1] hept-2-yl)cyclohexan-1-ol	3407-42-9	5-<10%	Eye Irrit. 2A-Aquatic Acute 1-Aquatic Chronic 2;H319- H400-H411
Cedrol methyl ether	19870-74-7	1-<5%	Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1; H317-H410
Patchouli alcohol	5986-55-0	1-<5%	Aquatic Acute 2-Aquatic Chronic 2;H411
Coumarin	91-64-5	1-<5%	Acute Tox. 4-Skin Sens. 1B-Aquatic Acute 3;H302- H317-H402
alpha-Guaiene	3691-12-1	1-<5%	Skin Irrit. 2-Eye Irrit. 2A-Asp. Tox 1;H304-H315-H319
2-Ethyl-4-(2,2,3-trimethyl-3- cyclopenten-1-yl)-2-buten-1-ol	28219-61-6	1-<5%	Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 2-Aquatic Chronic 2;H315-H319-H411
Dihydromyrcenol	18479-58-8	1-<5%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A- Aquatic Acute 3;H227-H303-H315-H319-H402
Isolongifolene ketone	23787-90-8	0.1-<1%	Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2; H317-H411
Cinnamaldehyde	104-55-2	0.1-<1%	Acute Tox. 5-Acute Tox. 4-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1A-Aquatic Acute 2-Aquatic Chronic 3;H303-H312-H315-H317-H319-H401-H412
beta-Caryophyllene	87-44-5	0.1-<1%	Skin Sens. 1B-Asp. Tox 1-Aquatic Chronic 4;H304- H317-H413
d-Limonene	5989-27-5	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1- Aquatic Acute 1-Aquatic Chronic 3;H226-H304-H315- H317-H400-H412
alpha-Cedrene	469-61-4	0.1-<1%	Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H304- H410
Acetyl cedrene	32388-55-9	0.1-<1%	Acute Tox. 5-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1;H303-H317-H410
Linalyl acetate	115-95-7	0.1-<1%	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2B-Skin Sens. 1B- Aquatic Acute 3;H227-H315-H317-H320-H402
alpha-iso-Methylionone	127-51-5	0.1-<1%	Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2; H317-H411



Version: 2 (01/10/2024)

# SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** AMBER RESIN + ROSEWOOD

Version: 2

delta-1-(2,6,6-Trimethyl-3- cyclohexen-1-yl)-2-buten-1-one 57378-68-4 <0.1%	Acute Tox. 4-Skin Irrit. 2-Skin Sens. 1A-Aquatic Acute 1-Aquatic Chronic 1;H302-H315-H317-H410
--	--

### Substances with workplace exposure limits, not listed above:

Not Applicable

#### Section 4. First-aid measures

# 4.1 Description of first aid measures

**Inhalation:** Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

**Eye exposure:** Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

**Skin exposure:** IF ON SKIN: Wash with plenty of soap and water.

**Ingestion:** Rinse mouth with water and obtain medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

# 5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

### 5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

### Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

### 6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

# 6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

#### 6.4 Reference to other sections:

Also refer to sections 8 and 13.

Page 4 (10)

Issue date: 01/10/2024

Version: 2 (01/10/2024)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

### Section 7. Handling and storage

### 7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

### 7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

### Section 8. Exposure controls/personal protection

#### 8.1 Control parameters

Workplace exposure limits: Not Applicable

#### 8.2 Exposure Controls

### **Eye / Skin Protection**

Wear protective gloves/eye protection/face protection

### **Respiratory Protection**

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

# Section 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance: Free flowing liquid without sediment

Odour:

Odour threshold:

Not determined

PH:

Not determined

Melting point / freezing point:

Not determined

Not determined

Not determined

Not determined

Flash point: > 93 °C

**Evaporation rate:** Not determined Flammability (solid, gas): Not determined

Issue date: 01/10/2024 Version: 2 (01/10/2024)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

Upper/lower flammability or explosive limits: Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Relative density: 0.9570 - 0.9670 Solubility(ies): Not determined Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined **Decomposition temperature:** Not determined Viscosity: Not determined **Explosive properties:** Not expected Not expected **Oxidising properties:** 

9.2 Other information:

Refractive Index @ 20C: 1.4741 - 1.4771

Flash Point (Fahrenheit): > 200 °F

Color Range: 5 Pale Yellow - 3 Very Pale Yellow

### Section 10. Stability and reactivity

### 10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

#### 10.2 Chemical stability:

Good stability under normal storage conditions.

### 10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

#### 10.4 Conditions to avoid:

Avoid extreme heat.

### 10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

#### 10.6 Hazardous decomposition products:

Not expected.

### Section 11. Toxicological information

# 11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

**Acute Toxicity:** Based on available data the classification criteria are not met.

Acute Toxicity Oral >5000
Acute Toxicity Dermal >5000

Issue date: 01/10/2024 Version: 2 (01/10/2024)

# SAFETY DATA SHEET

In accordance with UN GHS latest edition

AMBER RESIN + ROSEWOOD **Product:** 

2 Version:

Acute Toxicity Inhalation Not Available

Skin corrosion/irritation: Based on available data the classification criteria are not met. Serious eye damage/irritation: Based on available data the classification criteria are not met.

Respiratory or skin sensitisation: Sensitization - Skin Category 1

Germ cell mutagenicity: Based on available data the classification criteria are not met. Carcinogenicity: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. Reproductive toxicity: STOT-single exposure: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. STOT-repeated exposure: Based on available data the classification criteria are not met. **Aspiration hazard:** 

### Information about hazardous ingredients in the mixture

Ingredient	CAS	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
Benzyl benzoate	120-51-4	1500	4000	Not available	Not available
Coumarin	91-64-5	500	Not available	Not available	Not available
Dihydromyrcenol	18479-58-8	3600	Not available	Not available	Not available

Refer to Sections 2 and 3 for additional information.

# Section 12. Ecological information

### 12.1 Toxicity:

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available 12.3 Bioaccumulative potential: Not available 12.4 Mobility in soil: Not available 12.5 Other adverse effects: Not available

# **Section 13. Disposal considerations**

#### 13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# Section 14. Transport information

14.1 UN	14.2 UN Proper Shipping Name:	14.3	Sub Risk:	14.4. Packing
number:		Transport		Group:
		hazard class		
		(es):		



Version: 2 (01/10/2024)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedrol methyl ether, alpha-Cedrene)	9	-	III
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedrol methyl ether, alpha-Cedrene) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedrol methyl ether, alpha-Cedrene)	9	-	III
ICAO TI	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedrol methyl ether, alpha-Cedrene)	9	-	III

**14.5 Environmental hazards:** This is classified as an environmentally hazardous substance under the UN

Model Regulations. This is classified as a Marine Pollutant under the IMDG

Code.

**14.6 Special precautions for user:** None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

**Section 15. Regulatory information** 



Version: 2 (01/10/2024)

# SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

# Components listed on California's Proposition 65:

Name	CAS	%
Myrcene	123-35-3	<0.1%

### **Essential Oil Components:**

Name	CAS	%
PATCHOULI OIL MD	8014-09-3	10-<20%
CEDARWOOD OIL TEXAS ( R ) DARK	68990-83-0	1-<5%
ORANGE OIL FLORIDA	8028-48-6	0.1-<1%
THYME OIL WHITE	8007-46-3	<0.1%

# Additional formulation properties

Name	CAS	%
Vanillin	121-33-5	0.1-<1%

# Components listed on California's SB312

Name	CAS	%
DIOCTYL ADIPATE ( S ) "DOA"	103-23-1	50-100%
BENZYL BENZOATE	120-51-4	5-<10%
COUMARIN ( C )	91-64-5	1-<5%
CINNAMIC ALDEHYDE	104-55-2	0.1-<1%
METHYL IONONE GAMMA	127-51-5	0.1-<1%

US Department Of Transport Bulk Packing - Group:

# **Section 16. Other information**

**Concentration % Limits:** SCI 3=19.52% SS 1=14.29% EH A2=13.36% EH A3=1.33% EH C2=33.

80% EH C3=3.38%

**Total Fractional Values:** SCI 3=5.12 SS 1=7.00 EH A2=7.49 EH A3=74.96 EH C2=2.96 EH C3=29.

59

# Key to revisions:

2.1 Classification of the substance or mixture

Concentration % Limits


**GHS Workplace Exposure Limits** 

SECTION 3: Composition/information on ingredients

**Total Fractional Values** 

# Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 4	Acute Toxicity - Dermal Category 4
Acute Tox. 5	Acute Toxicity - Oral Category 5





# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

AMBER RESIN + ROSEWOOD **Product:** 

2 Version:

Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Aquatic Chronic 4	Hazardous to the Aquatic Environment - Long-term Hazard Category 4
Asp. Tox 1	Aspiration Hazard Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.



Version: 2 (01/10/2024)

# **SAFETY DATA SHEET**

In accordance with UN GHS latest edition

Product: AMBER RESIN + ROSEWOOD

Version: 2

P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391	Collect spillage.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Sens. 1A	Sensitization - Skin Category 1A
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.