Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

WOOD SAGE + SEA SALT **Product:**

1 Version:

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: WOOD SAGE + SEA SALT

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Of { æ 28/Á; æ 1 a 28 A 4 a 1 a 28 A 4 a 1 a 28 A 4 &\^æe^ æÁajā@@åÁj\[å*&dÀM•^Áæ&&[¦åāj*Áq[Á*•cæàjā@@åÁ^**jæe[¦^Á**ãã^jāj^•ÈÁZ[¦ÁTæ);*~æ&č¦āj*ÁM•^ÁU}j^È

1.3 Details of the supplier of the safety data sheet

Company name: Šæk\ÁQE@a; AÛ`]]|^ÁQ&Á HJÍÁT[}o&æn{ ÁOÆç^Á Company address:

Xã&q¦ãædŽÁÓÔÁ XÌ ZÁ ÙÌ

E-Mail address: @\||O|æ\\•`]]|^B&æÁ

ЀˀFÊÍ€Î Company phone: 1.4 Emergency telephone number

Emergency phone: Þ[¦c@ÁOE! ^¦æðæÁi€EÈEGIÈH€€EÁO;c^¦}æðái}æÁú€HĚGIÈHÌÌÏ

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Class and category of Flammable Liquid, Hazard Category 4 danger:

Skin Corrosion / Irritation Category 2 Sensitization - Skin Category 1

Hazardous to the Aquatic Environment - Acute Hazard Category 2 Hazardous to the Aquatic Environment - Long-term Hazard Category 1

H227, Combustible liquid. H315. Causes skin irritation.

H317, May cause an allergic skin reaction.

H401, Toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Signal word: Warning

Hazard statements: H227, Combustible liquid.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H401, Toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.



Version: 1 (12/29/2021)



SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

Precautionary statements:

P210, Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P261, Avoid breathing vapour or dust.

P264, Wash hands and other contacted skin thoroughly after handling.

P272, Contaminated work clothing should not be allowed out of the workplace.

P273, Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection. P302/352, IF ON SKIN: Wash with plenty of soap and water.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P362, Take off contaminated clothing and wash before reuse.

P370/378, In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

P391, Collect spillage.

P403/235, Store in a well-ventilated place. Keep cool.

P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.



Pictograms:

2.3 Other hazards

Other hazards: None

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	%	GHS Classification
Methyl dihydrojasmonate	24851-98-7	20-<50%	Aquatic Acute 3;H402
1-(1,2,3,4,5,6,7,8-Octahydro- 2,3,8,8-tetramethyl-2- naphthalenyl)ethanone	54464-57-2	20-<50%	Skin Irrit. 2-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 1;H315-H317-H401-H410
E- and Z-Oxacyclohexadec-12 (+13)-en-2-one	111879-80-2	5-<10%	Aquatic Acute 1-Aquatic Chronic 2;H400-H411
Ethylene brassylate	105-95-3	1-<5%	Aquatic Acute 2;H401
Cedrol methyl ether	19870-74-7	1-<5%	Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 1; H317-H410
1,3,4,6,7,8-Hexahydro- 4,6,6,7,8,8- hexamethylcyclopenta-gamma- 2-benzopyran	1222-05-5	1-<5%	Skin Irrit. 3-Aquatic Acute 1-Aquatic Chronic 1;H316- H410
Linalyl acetate	115-95-7	1-<5%	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2B-Skin Sens. 1B- Aquatic Acute 3;H227-H315-H317-H320-H402
3,3,5,5-Tetramethyl-4- ethoxyvinylcyclohexanone	36306-87-3	1-<5%	Skin Irrit. 2-Aquatic Acute 2-Aquatic Chronic 2;H315- H411



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

alpha-iso-Methylionone	127-51-5	1-<5%	Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H316-H317-H411
d-Limonene	5989-27-5	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 3;H226-H304-H315-H317-H400-H412
Linalool	78-70-6	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3;H227-H303-H315-H317-H319-H402
6,7-Dihydro-1,1,2,3,3- pentamethyl-4(5H)-indanone	33704-61-9	0.1-<1%	Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B- Aquatic Acute 2-Aquatic Chronic 2;H303-H315-H317- H319-H411
beta-Pinene	127-91-3	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317-H410
p-Mentha-1,4-diene	99-85-4	0.1-<1%	Flam. Liq. 3-Acute Tox. 5-Skin Irrit. 3-Repr. 2-Asp. Tox 1;H226-H303-H304-H316-H361
Oxacycloheptadec-10-ene-2-one	28645-51-4	0.1-<1%	Aquatic Acute 1-Aquatic Chronic 1;H410

Substances with workplace exposure limits, not listed above:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water.

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Clear Colorless - 2 Very Pale Yellow free-flowing liquid without

sediment

Odour: Conforms to Standard

Odour threshold:

pH:

Not determined

Not determined

Melting point / freezing point:

Not determined

Not determined

Not determined

Flash point: 82 °C

Evaporation rate: Not determined **Flammability (solid, gas):** Not determined

Upper/lower flammability or explosive limits: Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Relative density: 0.9570 - 0.9670 Solubility(ies): Not determined Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined **Decomposition temperature:** Not determined Not determined **Viscosity:** Not expected **Explosive properties:** Oxidising properties: Not expected

9.2 Other information:

Refractive Index @ 20C: 1.4671 - 1.4771

Flash Point (Fahrenheit): 180 °F Calculated VOC: 0.00

Color Range: Colorless to 2 Very Pale Yellow

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity:Based on available data the classification criteria are not met.

Acute Toxicity Oral Not Applicable
Acute Toxicity Dermal Not Applicable
Acute Toxicity Inhalation Not Available

Skin corrosion/irritation: Skin Corrosion / Irritation Category 2

Serious eye damage/irritation: Based on available data the classification criteria are not met.

Respiratory or skin sensitisation: Sensitization - Skin Category 1

Germ cell mutagenicity:

Based on available data the classification criteria are not met.

Carcinogenicity:

Based on available data the classification criteria are not met.

Reproductive toxicity:

Based on available data the classification criteria are not met.

STOT-single exposure:

Based on available data the classification criteria are not met.

STOT-repeated exposure:

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability:Not available12.3 Bioaccumulative potential:Not available12.4 Mobility in soil:Not available12.5 Other adverse effects:Not available



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class(es):	Sub Risk:	14.4. Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, Cedrol methyl ether)	9	-	III
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, Cedrol methyl ether) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, Cedrol methyl ether)	9	-	III
UN3082 ENVIRONMENTAL SUBSTANCE, LIQ (1,2,3,4,5,6,7,8-Octetramethyl-2-naph		ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, Cedrol methyl ether)	9	-	III

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN

Model Regulations. This is classified as a Marine Pollutant under the IMDG

Code.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

Components listed on California's Proposition 65:

Name	CAS	%
Myrcene (Naturally-Occurring)	123-35-3	<0.1%



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

Essential Oil Components:

Name	CAS	%
LEMON OIL CALIFORNIA	8008-56-8	1-<5%

Section 16. Other information

Concentration % Limits: EH A2=13.36% EH A3=1.31% EH C1=84.95% EH C2=8.21% EH C3=0.

82117448% EH C4=63.15% SCI 2=38.77% SCI 3=3.56% SS 1=4.66%

Total Fractional Values: EH A2=7.49 EH A3=76.05 EH C1=1.18 EH C2=12.18 EH C3=121.78 EH

C4=1.58 SCI 2=2.58 SCI 3=28.07 SS 1=21.46

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 5	Acute Toxicity - Oral Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H361	Suspected of damaging fertility or the unborn child (exposure route).
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.



Version: 1 (12/29/2021)

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: WOOD SAGE + SEA SALT

Version: 1

H412	Harmful to aquatic life with long lasting effects.	
P202	Do not handle until all safety precautions have been read and understood.	
P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.	
P233	Keep container tightly closed.	
P240	Ground/bond container and receiving equipment.	
P241	Use explosion-proof electrical, ventilating and lighting equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P261	Avoid breathing vapour or dust.	
P264	Wash hands and other contacted skin thoroughly after handling.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/eye protection/face protection.	
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P302/352	IF ON SKIN: Wash with plenty of soap and water.	
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.	
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308/313	IF exposed or concerned: Get medical advice/attention.	
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.	
P331	Do not induce vomiting.	
P332/313	If skin irritation occurs: Get medical advice/attention.	
P333/313	If skin irritation or rash occurs: Get medical advice/attention.	
P337/313	If eye irritation persists: Get medical advice/attention.	
P362	Take off contaminated clothing and wash before reuse.	
P363	Wash contaminated clothing before reuse.	
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.	
P391	Collect spillage.	
P403/235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.	
Repr. 2	Toxic to Reproduction Category 2	
Skin Irrit. 2	Skin Corrosion / Irritation Category 2	
Skin Irrit. 3	Skin Corrosion / Irritation Category 3	
Skin Sens. 1B	Sensitization - Skin Category 1B	

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.